

**Amendments to the Claims:**

This listing of the claims will replace all prior versions and listings of the claims in the application:

1. (Currently Amended) A method for testing a semiconductor memory device including nm memory cell ~~arrays~~ regions for respectively outputting x-bit data when n word lines and m column selecting signal lines are selected, and each half of the nm memory cell regions is a first memory cell array and a second memory cell array, wherein n, m, and x are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm, the method comprising:

extending y-bit data received through y data I/O pads to (nm×x)-bit data to write the x-bit data to each of the nm memory cell ~~arrays~~ regions in a test data write step; and

comparing the x-bit data output from each of the nm memory cell ~~arrays~~ regions to generate nm-bit comparison result data, and sequentially outputting y-bit comparison result data selected by selecting, by y bits generated from the first memory cell array or from the second memory cell array, the nm-bit comparison result data in response to a control signal to the y data I/O pads, respectively, in a test data read step,

wherein n is an integer equal or greater than 2, wherein m is an integer equal or greater than 4, wherein x and y are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm.

2. (Currently Amended) The method of Claim 1, wherein in the test data write step, when the x-bit data is written to the respective nm memory cell ~~arrays~~ regions, the x-bit data written to the respective nm memory cell ~~arrays~~ regions are same-bit data.

3. (Currently Amended) The method of Claim 1, wherein the test data read step ~~further~~ comprises:

respectively comparing the x-bit data output from each of the nm memory cell ~~arrays~~ regions to generate the nm-bit comparison result data in a comparing step; and

outputting the y-bit comparison result data selected by selecting, by y bits, the nm comparison result data in response to the control signal to the y data I/O pads in a selecting step.

4.-9. (Canceled).

10. (Currently Amended) A method for testing a semiconductor memory device including nm memory cell ~~arrays~~ regions for respectively outputting x-bit data when n word lines and m column selecting signal lines are selected, ~~wherein n, m, and x are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm, the~~ method comprising:

extending y-bit data received through y data I/O pads to (nm×x)-bit data to write the x-bit data to each of the nm memory cell ~~arrays~~ regions in a test data write step; and

comparing the x-bit data output from each of the nm memory cell ~~arrays~~ regions to generate nm-bit comparison result data, grouping and outputting the nm-bit comparison result data into y groups by bit data generated with respect to corresponding n word lines or with respect to corresponding m column selecting signal lines in response to a control signal, and outputting y-bit comparison result data generated by respectively comparing the y grouped bit data through the y data I/O pads in a test data read step,

wherein n is an integer equal or greater than 2, wherein m is an integer equal or greater than 4, wherein x and y are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm.

11. (Currently Amended) A semiconductor memory device, comprising:

nm memory cell ~~arrays~~ regions configured to respectively output x-bit data when n word lines and m column selecting signal lines are selected, and each half of the nm memory cell regions is a first memory cell array and a second memory cell array, wherein n, m, and x are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm;

a test data write circuit configured to extend y-bit data received through y data I/O pads to (nm×x)-bit data to write the x-bit data to each of the nm memory cell arrays regions; and

a test data read circuit configured to compare the x-bit data output from each of the nm memory cell arrays regions to generate nm-bit comparison result data, and sequentially output y-bit comparison result data selected by selecting, by y bits generated from the first memory cell array or from the second memory cell array, the nm-bit comparison result data in response to a control signal to the y data I/O pads, respectively,

wherein n is an integer equal or greater than 2, wherein m is an integer equal or greater than 4, wherein x and y are integers greater than 1, wherein nm comprises n multiplied by m, and wherein y is less than nm.

12. (Currently Amended) The device of Claim 11, wherein in the test data write circuit, when x-bit data is written to the respective nm memory cell arrays regions, the x-bit data written to the respective nm memory cell arrays regions are same-bit data.

13. (Currently Amended) The device of Claim 11, wherein the test data read circuit includes:

a comparator configured to respectively compare the x-bit data output from each of the nm memory cell arrays regions to generate the nm-bit comparison result data; and

a selecting circuit configured to output the y-bit comparison result data selected by selecting, by y bits generated from the first memory cell array or from the second memory cell array, the nm comparison result data in response to the control signal to the y data I/O pads.

14.-20. (Canceled).

21. (Currently Amended) A semiconductor memory device, comprising:  
nm memory cell arrays regions configured to respectively output x-bit data

when  $n$  word lines and  $m$  column selecting signal lines are selected, ~~wherein  $n$ ,  $m$ , and  $x$  are integers greater than 1, wherein  $nm$  comprises  $n$  multiplied by  $m$ , and wherein  $y$  is less than  $nm$ ;~~

a test data write circuit configured to extend  $y$ -bit data received through  $y$  data I/O pads to  $(nm \times x)$ -bit data to write the  $x$ -bit data to each of the  $nm$  memory cell ~~arrays~~ regions;

and

a test data read circuit configured to compare the  $x$ -bit data output from each of the  $nm$  memory cell ~~arrays~~ regions to generate  $nm$ -bit comparison result data, group and output the  $nm$ -bit comparison result data into  $y$  groups by bit data generated with respect to corresponding  $n$  word lines or with respect to corresponding  $m$  column selecting signal lines in response to a control signal, and output  $y$ -bit comparison result data generated by respectively comparing the  $y$  grouped bit data through the  $y$  data I/O pads,

wherein  $n$  is an integer equal or greater than 2, wherein  $m$  is an integer equal or greater than 4, wherein  $x$  and  $y$  are integers greater than 1, wherein  $nm$  comprises  $n$  multiplied by  $m$ , and wherein  $y$  is less than  $nm$ .

22. - 36. (Canceled).

37. (Currently Amended) The device of claim 21, wherein the test data read circuit includes:

a first comparator configured to respectively compare the  $x$ -bit data output from each of the  $nm$  memory cell ~~arrays~~ regions;

a selecting circuit configured to group and output the  $nm$ -bit comparison result data into  $y$  groups by bit data generated with respect to corresponding  $n$  word lines or with respect to corresponding  $m$  column selecting signal lines in response to the control signal;

and

a second comparator configured to output the  $y$ -bit comparison result data generated by respectively comparing the  $y$  grouped bit data through the  $y$  data I/O pads.

38. (Previously Presented) The device of claim 37, wherein y is set to at least n when n is greater than m and is set to at least m when m is greater than n.

39. (Currently Amended) The method of claim 10, wherein in the test data write step, when x-bit data are written to the respective nm memory cell ~~arrays~~ regions, the x-bit data written to the nm memory cell ~~arrays~~ regions are same-bit data.

40. (Currently Amended) The method of claim 39, wherein the test data read step ~~further~~ comprises:

respectively comparing the x-bit data output from each of the nm memory cell ~~arrays~~ regions in a first comparing step;

grouping and outputting the nm-bit comparison result data into y groups by bit data generated with respect to corresponding n word lines or with respect to corresponding m column selecting signal lines in response to a control signal; and

outputting the y-bit comparison result data generated by respectively comparing the y grouped bit data through the y data I/O pads.

41. (Previously Presented) The method of claim 40, wherein y is set to at least n when n is greater than m and is set to at least m when m is greater than n.